KIOSK SERIES

KALYPSO 60

Printer kiosk series 58/60 mm

The proven choice for a reliable compact kiosk solution










With years of printing technology experience, AXIOHM-TXCOM presents the KALYPSO Kiosk Series based on the proven CM/RM Premium Series including a state of the art controller board thus providing the smallest all- in-one printing solution on the market.

The KALYPSO Kiosk is designed to provide outstanding features: ultra-silent printing, **high quality thermal head** (more than 100 km of tickets), **top printing speed** up to 250 mm/s, **long lite autocutter** (1,5 Million cuts) with both full and partial cuts, optimized printing quality and a jam free paper output system. The printer can be powered in both 12 and 24V. It comes standard with both a USB2.0 and RS232 interface connection.









COMPACT & EASY TO INTEGRATE

The KALYPSO will satisfy the most demanding requirements.

Kiosk designers are looking for OEM products that will fit their demands in terms of reduced dimensions and a practical shape. The KALYPSO Kiosk Series has the crucial advantage of being extremely compact while



providing maximum flexibility in the integration process with an adjustable paper roll arm and different paper loading positions.

SUITABLE FOR HARSH ENVIRONMENTS

With the strong democratization of contactless payment, durable, fast and easy-to-integrate printers are needed to print receipt tickets. With a robust and reliable design the KALYPSO Kiosk Series is particularly adapted to kiosk and vending machine application (indoor & outdoor).





KALYPSO 60

Print kiosk series 58/60 mm



Characteristics	Unit	12 Volts	24 Volts	
Max Print Speed	mm/s	150	250	
Paper Width	mm	60	60	
Print Width	mm	56	56	
Resolution	Dots/mm DPI	8 203	8 203	
Number of dots	dot	448	448	
Paper Thickness	μm	60 to 190	60 to 190	en en
Operating Voltage Range	V	12	24	944
Mechanism Reliability	Km	> of 100	> of 100	
Dimensions (W*D*H)	mm	89 x 81 x 72	89 x 81 x 72	THE PLANTS
Cutter	mm	Guillotine auto-cutter (full & partial cuts)	Guillotine auto-cutter (full & partial cuts)	
Cutter Reliability		1.5 Million cuts	1.5 Million cuts	
Operating Temperature	°C/F	-20 to 60°C /-4 to 140 °F	-20 to 60°C / -4 to 140 °F	
Operating Humidity	%RH	20 to 85	20 to 85	
Interface		RS232 & USB 2.0	RS232 & USB 2.0	
Command Set		Compatible ESC/POS TM	Compatible ESC/POS TM	
User Flash memory	Kbytes	192	192	
Sensors		End of Paper Jam free paper detection	End of Paper Jam free paper detection	
Human interfaces		Paper Feed and Reset buttons LED indicator	Paper Feed and Reset buttons LED indicator	
Options		Paper Arm with 3 positions Paper Low sensor input Power and interface cables	Paper Arm with 3 positions Paper Low sensor input Power and interface cables	
Drivers		Windows TM XP / VISTA / Seven / Eight / CE – LINUX	Windows TM XP /VISTA / Seven / Eight / CE - LINUX	
Firmware Features		Compatible EASYFONT ™ Paper Low Management Top of form Management	Compatible EASYFONT ™ Paper Low Management Top of form Management	
Bar Code printing		1D and 2D	1D and 2D	



More than 30 years of innovations for you



Quality

100% of our printers are fully tested at the end of the production line. Our Return rate is below the industry standard: 0,3%!



Customization

Part of our DNA, Axiohm continues to support your project at every integration stage with specific proposals. Do not hesitate to contact us!



Delivery

Our factory and procurement department are doing their best to secure your shipment schedule. Reality speaks for itself, our service rate for 2018 is 97,6%!

France (for EMEA, Asia/Pacific)
Parc d'affaires NOVEOS – 10 avenue DESCARTES
92350 Le PLESSIS ROBINSON
Tel: +33 1 46 30 36 10 - info@axiohm.com

USA (for USA, Canada & South America)

455 Wards Corner Road Suite 500 Loveland, OH 45140 - USA Tel: +1 (513) 248-9900 - namsales@axiohm.com

